


升级款 | 履带车

产品简介

PRODUCT INTRODUCTION

品质改变世界

机器配置/MACHINE CONFIGURATION



浮动轮系
Floating gear train



加厚车厢
Thickened compartment



工程履带
Engineering track

参数配置/PARAMETER CONFIGURATION

| 产品名称 | 1.5吨座驾履带车(浮动轮、加高护栏) | 3.0吨座驾履带车(加高护栏) | 5.0吨座驾履带车(加高护栏) |
|-----------------------------------|---|--|---|
| product name | 1.5 ton seat track vehicle (floating wheel, raised guardrail) | Track vehicle with 3.0 ton seat (Raised guardrail) | Track vehicle 5.0 ton seat (Raised guardrail) |
| 型号 | YYT-1.5 | YYT-3 | YYT-5 |
| Model | | | |
| 外形尺寸 (mm) | 2750*1200*1400 | 3500*1600*2000 | 3700*1800*2000 |
| Dimensions (mm) | | | |
| 车厢尺寸 (mm) | 1600*1200*850 | 2200*1600*980 | 2350*1800*980 |
| Car size (mm) | | | |
| 发动机功率 (HP) | 12马力 | 32马力 | 57马力 |
| Engine power (HP) | | | |
| 底盘宽度 (mm) | 850 | 1600 | 1800 |
| Chassis width (mm) | | | |
| 驱动方式 | 柴油机 (水冷) | 柴油机 (水冷) | 柴油机 (水冷) |
| Drive mode | Diesel engine (water-cooled) | Diesel engine (water-cooled) | Diesel engine (water-cooled) |
| 变速箱材质型号 | 特定18 | 特定21 | 特定28 |
| Gearbox material model | 18 cast iron | 21 cast iron | 28 cast iron |
| 履带规格 (mm) | 300*72*56 | 320*90*56 | 400*90*62 |
| Track specifications (mm) | | | |
| 履带材质 | 工程橡胶履带 | 工程橡胶履带 | 工程橡胶履带 |
| Track material | Engineering rubber track | Engineering rubber track | Engineering rubber track |
| 整车自重 (kg) | 930 | 2000 | 2400 |
| Vehicle weight (kg) | | | |
| 启动方式 | 电启/手摇 | 电启/手摇 | 电启 |
| Start way | Electric start / hand crank | Electric start / hand crank | Electric start |
| 额定载重 (t) | 1.5 | 3 | 5 |
| Rated load (t) | | | |
| 液压自卸功能 | 有 | 有 | 有 |
| Hydraulic self-unloading function | Have | Have | Have |
| 最小离地间隙 (mm) | 500 | 600 | 600 |
| Minimum ground clearance (mm) | | | |
| 驻坡角 | 35° | 35° | 35° |
| Standing angle | | | |
| 上坡角 | 45° | 45° | 45° |
| Uphill angle | | | |
| 行驶速度 (km/h) | 0.8-12 | 2.3-13 | 0-15 |
| Driving speed (km/h) | | | |

性能特点/PERFORMANCE CHARACTERISTICS

- ◎ 使用范围广，结构简单，传动平稳，操作省力，易实现自动化控制
Wide range of use, simple structure, stable transmission, low effort, easy to achieve automatic control
- ◎ 采用国内知名厂家动力系统，动力大，油耗低，易操作维护
The use of domestic well-known manufacturers power system, large power, low fuel consumption, easy to operate and maintain.
- ◎ 转向采用液压助力，更省力，转弯半径小，机动灵活，尤其适应狭窄场地，复杂地形
Steering with hydraulic power, more labor-saving, small turning radius, flexible maneuverability, especially suitable for narrow places and complex terrain
- ◎ 配备电启动，手柄集中，操作方便
Equipped with electric start, centralized handle, easy to operate

升级款 | 履带车

产品简介

PRODUCT INTRODUCTION

品质改变世界



性能技术参数

PERFORMANCE TECHNICAL PARAMETERS

型号: YYT-1.5
Model: YYT-1.5
总长度: 2750mm
Total length: 2750mm
总宽: 1200mm
Total width: 1200mm
总高: 1400mm
Total height: 1400mm
自重: 930kg
Self-respect: 930kg
额定载重: 1500kg
Rated load: 1500kg



性能技术参数

PERFORMANCE TECHNICAL PARAMETERS

型号: YYT-3
Model: YYT-3
总长度: 3500mm
Total length: 3500mm
总宽: 1600mm
Total width: 1600mm
总高: 2000mm
Total height: 2000mm
自重: 2000kg
Self-respect: 2000kg
额定载重: 3000kg
Rated load: 3000kg



性能技术参数

PERFORMANCE TECHNICAL PARAMETERS

型号: YYT-5
Model: YYT-5
总长度: 3700mm
Total length: 3700mm
总宽: 1800mm
Total width: 1800mm
总高: 2000mm
Total height: 2000mm
自重: 2400kg
Self-respect: 2400kg
额定载重: 5000kg
Rated load: 5000kg

产品用途范围广，性能优越，坚固耐用，不仅能适用于水稻田、沼泽地、泥泞的田间道路、崎岖的山路、松软的草地、山林和沙漠、湿滑的冰面和雪地等复杂恶劣路况，也适用于农林果园运输、货场装载、水利建设、其他建工程、矿山场所应用也非常广泛。经常出口东南亚、非洲、欧洲、等多个国家和地区。
The product has a wide range of uses, superior performance, strong and durable, can not only be applied to paddy fields, swamps, muddy field roads, rugged mountain roads, soft grassland, mountain forest and desert, slippery ice and snow and other complex and harsh road conditions, also suitable for agriculture, forestry and orchard transportation, freight yard loading, water conservancy construction, other construction projects and mining sites are also widely used. Often exported to Southeast Asia, Africa, Europe, and other countries and regions.