Engine Xinchai

C490BPG / 2.67 L

Fuel Type Diesel Capacity @ 500 mm LC 2,000 kg

CPCD20 DIESEL PNEUMATIC TIRE FORKLIFTS





CPCD20 SPECIFICATIONS >>>

General	Model	1			CPCD20
	Power Type	2			Diesel
	Base Capacity	3	@rated load center	kg	2,000
	Load Center	4		mm	500
Weights	Service Weight	5	unloaded	kg	3,355
	Axie Load	6	loaded / unloaded, front	kg	4,685/1,345
		7	loaded / unloaded, rear	kg	670/2,010
Tires	Tire Type	8			Pneumatic
	Wheels	9	front / rear		2/2
	Wheelbase	10		mm	1,650
	Tire Size	11	front		7.00-12-12PR
		12	rear		6.00-9-10PR
	Tread Width	13	front / rear		960/970
Mast	Max. Fork Height	14	with std 2-stage mast	mm	3,000
	Free lift	15	with std 2-stage mast	mm	140
	Height, Upright Lowered	16	with std 2-stage mast	mm	2,070
	Height, Upright Extended	17	with std 2-stage mast	mm	4,025
	Mast Tilt, Fwd/Back	18	with std 2-stage mast	deg	6° /12°
	Carriage	19	width	mm	1,100
	Fork Spread	20	minimum / maximum	mm	272/1,072
	Fork Dimensions	21	TxWxL	mm	40x100x1,070
Chassis	Length to Fork Face	22	with std 2-stage mast	mm	2,590
	Overall Width	23		mm	1,150
	Overhead Guard Height	24		mm	2,100
	Turning Radius	25	minimum outside	mm	2,190
	Fork Overhang	26	with std 2-stage mast	mm	458
	Right Angle Stack	27	add load length and clearance	mm	3,935
	Ground Clearance	28	minimum loaded	mm	110
		29	center of wheelbase	mm	120
Performance	Travel Speed	30	loaded / unloaded	km/h	19/20
	Lift Speed	31	loaded / unloaded	m/s	0.53/0.55
	Lower Speed	32	loaded / unloaded	m/s	0.42/0.51
	Max. Drawbar Pull	33	loaded	kg	1,680
	Max. Gradeability	34	loaded / unloaded	%	18/20
Systems	Brakes	35	service		Foot/Hyd
		36	parking		Hand/Mech
	Engine	37	manufacturer		Xinchai
		38	model		C490BPG
		39	emission compliance		CHN Stage II
		40	cylinders		4
		41	displacement	liters	2.67
		42	rated power	kW/rpm	40/2650
		43	Max. torque	N · m/rpm	160/1800



